



## FITUR

- Layar 12.1 " LCD TFT dengan Resolusi Tinggi
- Pengoperasian yang Mudah: Layar Dapat Dilipat, Terdapat Rak Untuk Probe Dan Terdapat Pegangan Sehingga Mudah Untuk Dibawa, Bersahabat Dengan Pengguna GUI Dengan 3 Mode Tampilan Dan 4 Pemilihan Warna Background
- Fungsi yang Power Full : 24 Jam Penyimpanan CTG, Dapat Mencetak Deskripsi Grafik dengan Cepat "Smart Note" ,Sinyal Verifikasi Overlap, Real-Time, Dan Offline Transmisi Data Ke PC
- Transduser dengan pengukuran akurat yang terbuat dari 12-Kristal dan 1Mhz Anti Air
- Baterai Lithium Sehingga Dapat Diisi Ulang Secara Otomatis, Power Supply Dapat Bekerja Selama 2-4 Jam
- Sudut Kemiringan LCD dapat Diatur Hingga Maksimal 60 derajat
- Dapat Melakukan Pengukuran. Meliputi : FHRS Kembar, Aktifitas Janin Pada Uterus, Pergerakan Janin, Tekanan Intrauterine, DECG (optional) & NIBP, SPO2, HR, ECG, Temp
- Support Wireless Twins Fetal Monitoring & Support Wireless Deteksi DECG/MECG (optional)
- Transduser Anti Air Tipe IPX8
- Komunikasi Port Dengan Ethernet, RS232



**CPAKB**

CARA PEMBUATAN  
ALAT KESEHATAN  
YANG BAIK

HK.02.04/VI/011/2016

**PT. SINKO PRIMA ALLOY**



### SPESIFIKASI

Model	MATERNAL MED-02		
Monitor	Dimension	347 (L)x 330 (W)x 126(H)	
	Weight	Approx 6,3 kg	
	Power Supply	Operating Voltage	110V-240V
		Operating Frequency	50Hz/60Hz
		Input Power	0,2 A - 1 A
		Battery	14,8VDC/5000mAh
	Standards Compliance		IEC 60601-1:2005, EN60601-1:2006/AC:2010
			IEC 60601-1-2:2007, EN60601-1-2:2007/AC:2010
			IEC/EN60601-2-27
			IEC/EN60601-2-37
			IEC/EN60601-2-49
			IEC 80601-2-30
			ISO 80601-2-61
			ISO 80601-2-56
			EN 12470-4
	AAMI/ANSI EC 13		
	Anti Electric Shock Type	Class I equipment with internal power supply	
Anti Electric Shock Degree	BF	FHR1, FHR2, TOCO, FM, IUP (optional)	
	BF (Defibrillating-proof)	SPO2, NIBP	
	CF	DECG (Optional)	
	CF (Defibrillating-proof)	ECG, TEMP	
Degree of Protection against Harmful Ingress of Water		Main Unit : IPX1, protected against vertically falling water drops (provided recorder drawer is shut and the monitor is not mounted on the wall vertically). US/TOCO Transducers: IPX8, protected against the effects of continuous emersion in water	
Degree of Safety in Presence of Flammable Gases		Equipment not suitable for use in presence of flammable gases	
Disinfection/Sterilizing Method		Refer to this user manual for details	
EMC		CISPR11 Group 1 Class A	
Working System		Continuous running equipment	
Display	Screen	12,1 Inch	
	Pixel	800(H)x600(V)	
Signal Interface	RS232 interface (DB9 or D-Sub), RJ45 interface	RS232 interface (DB9 or D-Sub), RJ45 interface	
Ultrasound Transducer	Cable Length	2,5m	
	Weight	190 g	
	Dimension	88mm x 35mm	
TOCO Transducer	Cable Length	2,5m	
	Weight	180 g	
	Dimension	88mm x 35mm	
Remote Even Marker	Length	2,5 m	
	Weight	± 60 g	
ECG	Cable Length	3 m	
	Weight	185 g	
SPO2	Cable Length	3,5mm x 2580mm (2,5mm)	
	Weight	82,5 g	
NIBP	Cable Length	7mm x 3000mm	
	Weight	126 g (tanpa cuff / cek lagi yang dengan cuff seperti apa)	
Temp	Cable Length	3mm x 3000mm	
	Weight	55 g	